ASSOCIATION CONNECTING	© Convright 2005 IPC Bannockburn Illinois All rights reserved under both			nder both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with lower level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
1752-21.1	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e*	* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materi					als and Mfg Information				
Supplier Informa	ation														
Company name*			Company unique ID				Unique ID Authority					Response Date*			
onsemi											2023-06-08				
Contact Name	Title - Contact				Phone - Contact*				Email -	Email - Contact*					
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Authorized Representative*			Title - Representative				Phone - Representative*				Email - Representative*				
Product-Env-Stewards			Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Requester	Requester Item Number Mfr Item		n Number Mfr Item Name				Effective Date	e Version	Ν	Manufacturing Site		Weight*	UOM	Unit Type	
		NCP333FCT2G 1.5A Load sw		1.5A Load switch	ch with discharge path		2023-06-08		C	CNG		0.7397	mg	Each	
Manufacturing P	Proccess Information	1									1				
Terminal Plating / Grid Array Material Term			erminal Base A	rminal Base Alloy J-STD-020 MSL		L Rating	Peak Process Body Temperature Ma		e Max Time at Peak	Tempera	ture Numb	er of Reflow Cy	cles		
SnAgCu CU			U Alloy 1			260		C	30	seconds 3					
Comments															
level 1 - maximum tir	me at peak temperature o	luring sol	dering is 10-3	0 seconds											
or more information	n regarding material con	position j	please refer to	page 3											

RoHS Material Composition Declaration				Declaration Type *	Detailed						
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Disobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of						
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted						
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.											
Exemption List Version	EL-2011/534/EU										
Declaration Signature											
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the						
Supplier Digital Signature Ra	stislav Drska	Le									

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

sigma range of distribution unless othe		of the substance of the fi	W concentration	i [i ] Optionally enter the positive (	() and negative () toterance in percer	in (1966: percen	a tolerance varues are	expected to cover a 5
Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.483	mg	Supplier	Silicon (Si)	7440-21-3		0.483	mg
Protection coat	0.0056	mg		Polyimide	proprietary data		0.0056	mg
Solder Ball	0.241	mg	Supplier	Silver (Ag)	7440-22-4		0.0096	mg
			Supplier	Tin (Sn)	7440-31-5		0.2302	mg
			Supplier	Copper (Cu)	7440-50-8		0.0012	mg
Under Bump Metal	0.0101	mg	Supplier	Titanium (Ti)	7440-32-6		0.002	mg
			Supplier	Copper (Cu)	7440-50-8		0.0081	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3