



Product/Process Change Notice - PCN 18_0147 Rev. -

Analog Devices, Inc. Three Technology Way Norwood, Massachusetts 02062-9106

This notice is to inform you of a change that will be made to certain ADI products (see Appendix A) that you may have purchased in the last 2 years. **Any inquiries or requests with this PCN (additional data or samples) must be sent to ADI within 30 days of publication date.** ADI contact information is listed below.

PCN Title: AD75019 Operational Temperature Clarification

Publication Date: 10-Sep-2018

Effectivity Date: 10-Sep-2018 *(the earliest date that a customer could expect to receive changed material)*

Revision Description:

Initial Release

Description Of Change:

AD75019 Operational Temperature Range correction. Remove mention of -25 to +85 degC operating temperature from the specification table.

Reason For Change:

To correct a typographic error regarding the operating temperature range of the device that conflicted with the correct operating temperature range of 0 to 70 deg C referred to in the Absolute Maximum Rating and ordering guide of the datasheet.

Impact of the change (positive or negative) on fit, form, function & reliability:

No change in fit, form, function or reliability of the product.

Summary of Supporting Information:

Attached is a document outlining the changes from Rev. C to Rev. D of the datasheet

Supporting Documents

Attachment 1: Type: Datasheet Specification Comparison

ADI_PCN_18_0147_Rev_-_AD75019.pdf

For questions on this PCN, please send an email to the regional contacts below or contact your local ADI sales representatives.

Americas:
PCN_Americas@analog.com

Europe:
PCN_Europe@analog.com

Japan:
PCN_Japan@analog.com

Rest of Asia:
PCN_ROA@analog.com

Appendix A - Affected ADI Models

Added Parts On This Revision - Product Family / Model Number (3)

AD75019 / AD75019JP

AD75019 / AD75019JPZ

AD75019 / AD75019JPZ-REEL

Appendix B - Revision History

Rev	Publish Date	Effectivity Date	Rev Description
Rev. -	10-Sep-2018	10-Sep-2018	Initial Release

Analog Devices, Inc.

DocId:4512 Parent DocId:None Layout Rev:7

PCN 18_0147 - AD75019 operational temperature clarification

Datasheet change from Rev. C to Rev. D

The below section of the spec table will be removed. The operating and storage temperature ranges will remain in the Absolute Maximum Ratings and in the Ordering Guide.

TEMPERATURE RANGE	T_{MIN} , T_{MAX}			
Operating		-25	+85	°C
Storage		-65	+150	°C