

LINEAR TECHNOLOGY MATERIALS DECLARATION

1t3082ist#trpbf

(Engineering Calculation)

SOT-223

(printed on: 2020-07-11 20:27:32)

TOTAL MASS (g) : 0.114087

| COMPONENT MATERIAL | VENDOR/ INDUSTRY NAMES | CONSTITUENT NAME | CAS NUMBER | CONSTITUENT MASS (g) | CONSTITUENT (PPM) OF MATERIAL | CONSTITUENT (PPM) OF TOTAL PKG. | | |
|--------------------------------|--------------------------------------|--------------------------------|------------|----------------------|-------------------------------|---------------------------------|----------------|----------------------|
| Active Device | Linear Technology | Silicon (Si) | 7440-21-3 | 0.000881 | 1000000 | 7722.14990234 | | |
| Die Coat | Dow Corning | Silicone | 69430-27-9 | 0.000000 | 0 | 0 | | |
| Lead Frame | Cu | Copper (Cu) | 7440-50-8 | 0.062693 | 975000 | 549517.3125 | | |
| | | Iron (Fe) | 7439-89-6 | 0.001543 | 24000 | 13524.7197266 | | |
| | | Phosphorus (P) | 7723-14-0 | 0.000019 | 300 | 166.538986206 | | |
| | | Zinc (Zn) | 7440-66-6 | 0.000045 | 700 | 394.43447876 | | |
| | | Nickel (Ni) | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Silicon (Si) | 7440-21-3 | 0.000000 | 0 | 0 | | |
| | | Magnesium (Mg) | 7439-95-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000000 | 0 | 0 | | |
| Lead Frame Total: | | | | 0.064300 | 1000000 | 563603.0625 | | |
| Plating | PMI | Exter. Plating Pb | 7439-92-1 | 0.000000 | 0 | 0 | | |
| | | Exter. Plating Sn | 7440-31-5 | 0.001609 | 1000000 | 14106.6416016 | | |
| | | External Plating Total: | | | | 0.001609 | 1000000 | 14106.6416016 |
| | | Inter. Plating Ni | 7440-02-0 | 0.000000 | 0 | 0 | | |
| | | Inter. Plating Ag | 7440-22-4 | 0.000514 | 1000000 | 4505.31835938 | | |
| Internal Plating Total: | | | | 0.000514 | 1000000 | 4505.31835938 | | |
| Die Attach | Solder Wire Dia 0.3mm *100m 95Pb/5Sn | Silver (Ag) | 7440-22-4 | 0.000000 | 0 | 0 | | |
| | | Tin (Sn) | 7440-31-5 | 0.000037 | 50000 | 324.312805176 | | |
| | | Lead (Pb) | 7439-92-1 | 0.000709 | 950000 | 6214.53369141 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.000000 | 0 | 0 | | |
| | | Indium (In) | 7440-74-6 | 0.000000 | 0 | 0 | | |
| | | Metal Oxide | | 0.000000 | 0 | 0 | | |
| | | Antimony (Sb) | 7440-36-0 | 0.000000 | 0 | 0 | | |
| | | Resin (EP) | | 0.000000 | 0 | 0 | | |
| Die Attach Total: | | | | 0.000746 | 1000000 | 6538.84667969 | | |
| Encapsulation | MULTI-AROMATIC RESIN Br/Sb FREE | Resin (EP) | | 0.004738 | 103000 | 41529.5664062 | | |
| | | Bromine (Br) | 40039-93-8 | 0.000000 | 0 | 0 | | |
| | | Silica (SiO2) | 60676-86-0 | 0.041170 | 895000 | 360863.71875 | | |
| | | Antimony Trioxide (Sb2O3) | 1309-64-4 | 0.000000 | 0 | 0 | | |
| | | Metal Hydroxide | | 0.000000 | 0 | 0 | | |
| | | Carbon Black (C) | 1333-86-4 | 0.000092 | 2000 | 806.399353027 | | |
| | | Encapsulation Total: | | | | 0.046000 | 1000000 | 403199.6875 |
| Bond Wire Estimated | AFW/TANAKA/ Kn | Gold (Au) | 7440-57-5 | 0.000037 | 1000000 | 324.312805176 | | |
| | | | | | TOTAL MASS (g) : | 0.114087 | | |