



Product / Process Change Notification (PCN)

- Major change
 Minor change

PCN #: PCN_UtPoEH_20230701

Affected Series: WE-UtPoEH; 749119XXX

PCN Date: April 01, 2022

Effective Date: July 01, 2022

Change Category:

- Equipment / Location
 General Data
 Material
 Process
 Product Design
 Shipping / Packaging
 Supplier
 Software

Contact: Product Management

Phone: +49 (0) 7942 - 945 5001

Fax: +49 (0) 7942 - 945 5179

E-Mail: pcn.eisos@we-online.com

Data Sheet Change:

Yes No

Attachment:

Yes No

Description and purpose of change:

In order to enhance the product reliability, Würth Elektronik will update insulation tape of the transformer from 3M 1388Y-1 polyester film tape to Jingjiang Yahua PF*(d)(g) polyimide film tape.

In addition, the marking will be updated from ink to laser marking.

Finally, the AEC-Q200 qualification stamp will be added to the datasheet.

All products with date code 2023-07-12 or later, will be affected by this change.

There will be no change in fit, function, or quality of the product.

Detail of Change:

- The insulation tape will be updated

From	To
3M 1388Y-1 (E17385) polyester film tape	Jingjiang Yahua PF*(d)(g) (E165111) polyimide film tape

- Marking will be updated

From	To
Ink Marking	Laser Marking

- An AEC-Q200 stamp will also be added to the datasheet



Reliability / Qualification Summary:

- High Temperature Exposure: Reference Standard: MIL-STD-202-108 @ 125°C, 1000h
- Temperature Cycling: Reference Standard: JESD22 Method JA-104 @ -40°C(30min) – 125°C(30min), max transfer time 1min, 1000 cycles
- Biased Humidity: Reference Standard: MIL-STD-202-103 @ 85°C, 85%RH, 1000h
- External Visual: Reference Standard: MIL-STD-883-2009
- Physical Dimension: Reference Standard: JESD22 Method JB-100
- Resistance to Solvents: Reference Standard: MIL-STD-202-215
- Mechanical Shock: Reference Standard: MIL-STD-202-213 @ Shocks in each direction(x, -x, y, -y, z, -z) , peak value 100g's, duration 6ms, half-sine, velocity change 12.3ft/sec.
- Vibration: Reference Standard: MIL-STD-202-204 @ 10g's for 20min, 12cycles each of 3 orientations, test from15~2000HZ
- Resistance to Solder Heat: Reference Standard: J-STD-020 @ 245°C, tp=30~35s, 5 times reflow
- Solderability: Reference Standard: IPC-A-610 @ Steam Aging 8 hrs±15min @93°C, Tc=240~245°C, tp=20~30s.
- Board Flex: Reference Standard: AEC-Q200-005 @ bending 2mm (Min), 60(+5) sec
- Terminal Strength(SMD) : Reference Standard: AEC-Q200-006 @ Push off Force 17.7N
- Low Temperature Storage Life: Reference Standard: JESD22-A119 @ -40°C, 1000h