Notification Number:		20160810000			Notification Date:			Sept. 16, 2016			
Title	e: Datasheet fo	or BQ24	4080-Q	21/E	8Q24081-Q1						
Customer Contact: PCN Ma		<u>Manager</u>		Dept:	Quality Ser	Quality Services					
Cha	nge Type:										
	Assembly Site		Design				Wafer Bump Site				
	Assembly Process			Data Sheet			Wafer Bump Material				
	Assembly Materials			Part number change			Wafer Bump Process				
	Mechanical Specification				Test Site			Wafer Fab Site			
Packing/Shipping/Labeling			Test Process			\square	Wafer Fab Materials Wafer Fab Process				
<u> </u>				Notification Details				vva			
Des	Description of Change:										
bq24	product datashee			d as	seen in the	change revisio	n hi	story	TEXAS INSTRUMENTS		
	SLUSCB6A - MAY 2015-REVISED AUGUST 2016 www.ti.com										
Cha	Changes from Original (May 2016) to Revision A Page										
 Recommended Operating Conditions, Changed The T_J MIN value From: 0 To: -40°C											
• E	Electrical Characteristics,	Changeo	the con	dition	s statement From:	$0^{\circ}C \le T_J \le 125^{\circ}C$	To: -4	40°C ≤	⊊T _J ≤ 125°C5		
• E	Electrical Characteristics,	Changeo	the con	dition	s statement From:	$0^{\circ}C \le T_J \le 125^{\circ}C$	To: -4	40°C ≤			
• E	Electrical Characteristics,	Changeo Changeo	I the cond	dition dition	s statement From: s statement From:	$0^{\circ}C \le T_J \le 125^{\circ}C$	To: -4	40°C ≤	⊊T _J ≤ 125°C5		
• E • E <u>The</u>	Electrical Characteristics, Electrical Characteristics,	Changeo Changeo	I the cond	dition dition	s statement From: s statement From:	$0^{\circ}C \leq T_{J} \leq 125^{\circ}C$ $0^{\circ}C \leq T_{J} \leq 125^{\circ}C$	To: -4 To: -4	40°C ≤ 40°C ≤	⊊T _J ≤ 125°C5		
• E • E The De	Electrical Characteristics, Electrical Characteristics, datasheet numbe	Changed Changed r will be	I the cond	dition dition	s statement From: s statement From:	$0^{\circ}C \leq T_{J} \leq 125^{\circ}C$ $0^{\circ}C \leq T_{J} \leq 125^{\circ}C$	To: -4 To: -4	40°C ≤ 40°C ≤ hang	≤ T _J ≤ 125°C5 ≤ T _J ≤ 125°C6		
• E • E The Dev BQ Thes	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family	Changed Changed r will be 81-Q1 e review	the cond the cond e chan- wed at	dition dition ginc the	s statement From: s statement From: Change Fro SLUSCB6 datasheet lir	$0^{\circ}C \le T_{J} \le 125^{\circ}C^{-1}$ $0^{\circ}C \le T_{J} \le 125^{\circ}C^{-1}$	To: -4 To: -4	40°C ≤ 40°C ≤ hang	s T _J ≤ 125°C5 s T _J ≤ 125°C6 e To:		
• E • E De BQ Thes http	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family 24080-Q1/BQ2400 se changes may be	Changed Changed r will be 81-Q1 e review	the cond the cond e chan- wed at	dition dition ginc the	s statement From: s statement From: Change Fro SLUSCB6 datasheet lir	$0^{\circ}C \le T_{J} \le 125^{\circ}C^{-1}$ $0^{\circ}C \le T_{J} \le 125^{\circ}C^{-1}$	To: -4 To: -4	40°C ≤ 40°C ≤ hang	s T _J ≤ 125°C5 s T _J ≤ 125°C6 e To:		
• E • E De BQ Thes http	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family 24080-Q1/BQ2400 se changes may bo ://www.ti.com/lit/	Changed Changed r will be 81-Q1 e review ds/sym	the cond the cond e chan- wed at hlink/b	dition dition ging the q24	s statement From: s statement From: Change Fro SLUSCB6 datasheet lir 081-q1.pdf	$0^{\circ}C \le T_{J} \le 125^{\circ}C^{-1}$ $0^{\circ}C \le T_{J} \le 125^{\circ}C^{-1}$	To: -4 To: -4	40°C ≤ 40°C ≤ hang	s T _J ≤ 125°C5 s T _J ≤ 125°C6 e To:		
• E • E The De BQ Thes http Rea To n	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family 24080-Q1/BQ2400 se changes may bo ://www.ti.com/lit/ ason for Change: more accurately re	Changed Changed r will be 81-Q1 e review ds/syn	the cond the cond e chan wed at hlink/b	dition dition ginc the q24 hara	s statement From: s statement From: Change Fro SLUSCB6 datasheet lir 081-q1.pdf	$0^{\circ}C \le T_{J} \le 125^{\circ}C^{\circ}$ $0^{\circ}C \le T_{J} \le 125^{\circ}C^{\circ}$ om: hks provided.	To: -4 To: -4	40°C ≤ 40°C ≤ hang LUS	s T _J ≤ 125°C5 s T _J ≤ 125°C6 e To:		
 <i>E</i> <i>E</i> <i>E</i> <i>De</i> <i>De</i> <i>BQ</i> <i>BQ</i>	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family 24080-Q1/BQ2400 se changes may be c://www.ti.com/lit/ ason for Change: more accurately re icipated impact	Changed Changed r will b 81-Q1 e review ds/sym flect de on Fit,	the cond the cond e chan- wed at hlink/b evice cl	dition dition ging the q24 hara , Fu	s statement From: s statement From: Change Fro SLUSCB6 datasheet lir 081-q1.pdf acteristics.	$0^{\circ}C \le T_{J} \le 125^{\circ}C^{\circ}$ $0^{\circ}C \le T_{J} \le 125^{\circ}C^{\circ}$ om: hks provided.		40°C ≤ 40°C ≤ hang LUS (pc	s T _J ≤ 125°C5 s T _J ≤ 125°C6 le To: CB6A		
 E E The Dev BQ Thes http Rea To m Ant No a to th 	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family 24080-Q1/BQ2400 se changes may be ://www.ti.com/lit/ ison for Change: more accurately re icipated impact anticipated impact	Changed Changed <u>81-Q1</u> e revie ds/syn flect de on Fit,	the cond the cond e chan wed at hlink/b evice cl Form s a spe	dition dition ginc the q24 hara , Fu	s statement From: s statement From: Change From: SLUSCB6 datasheet lin 081-q1.pdf acteristics.	0°C ≤ T _J ≤ 125°C 0°C ≤ T _J ≤ 125°C om: hks provided.	To: To: C S S	40°C ≤ 40°C ≤ hang LUS / (pc	s T _J ≤ 125°C 5 s T _J ≤ 125°C 6 te To: CB6A Desitive / negative):		
 E E The Dev BQ Thes http Rea To m Ant No a to th 	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family 24080-Q1/BQ2400 se changes may be ://www.ti.com/lit/ ison for Change: more accurately re icipated impact he actual device inges to product	Changed Changed <u>81-Q1</u> e revie ds/syn flect de on Fit,	the cond the cond e chan wed at hlink/b evice cl Form s a spe	dition dition ginc the q24 hara , Fu	s statement From: s statement From: Change From: SLUSCB6 datasheet lin 081-q1.pdf acteristics.	0°C ≤ T _J ≤ 125°C 0°C ≤ T _J ≤ 125°C om: hks provided.	To: To: C S S	40°C ≤ 40°C ≤ hang LUS / (pc	s T _J ≤ 125°C 5 s T _J ≤ 125°C 6 te To: CB6A Desitive / negative):		
 <i>E</i> <i>E</i> <i>E</i> <i>Dev</i> <i>BQ</i> <i>BQ</i>	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family 24080-Q1/BQ2400 se changes may be ://www.ti.com/lit/ ison for Change: more accurately re icipated impact he actual device inges to product	Changed Changed <u>81-Q1</u> e revie ds/syn flect de on Fit,	the cond the cond e chan wed at hlink/b evice cl Form s a spe	dition dition ginc the q24 hara , Fu	s statement From: s statement From: Change From: SLUSCB6 datasheet lin 081-q1.pdf acteristics.	0°C ≤ T _J ≤ 125°C 0°C ≤ T _J ≤ 125°C om: hks provided.	To: To: C S	40°C ≤ 40°C ≤ hang LUS / (pc	s T _J ≤ 125°C 5 s T _J ≤ 125°C 6 te To: CB6A Desitive / negative):		
 <i>E</i> <i>E</i> <i>E</i> <i>De</i> <i>De</i> <i>BQ</i> <i>BQ</i>	Electrical Characteristics, Electrical Characteristics, datasheet number vice Family 24080-Q1/BQ2400 se changes may be ://www.ti.com/lit/ soon for Change: more accurately re icipated impact he actual device inges to product	Changed Changed <u>81-Q1</u> e revie ds/syn flect de on Fit,	the cond the cond e chan wed at hlink/b evice cl Form s a spe	dition dition ginc the q24 hara , Fu	s statement From: s statement From: Change Fro SLUSCB6 datasheet lir 081-q1.pdf acteristics. Inction, Qua cation change	0°C ≤ T _J ≤ 125°C 0°C ≤ T _J ≤ 125°C om: hks provided.	To: To: C S illity nt of catio	40°C ≤ 40°C ≤ hang LUS / (pc	s T _J ≤ 125°C 5 s T _J ≤ 125°C 6 te To: CB6A Desitive / negative):		

For questions regarding this notice, e-mails can be sent to the regional contacts shown below or your local Field Sales Representative.

Location	E-Mail
USA	PCNAmericasContact@list.ti.com
Europe	PCNEuropeContact@list.ti.com
Asia Pacific	PCNAsiaContact@list.ti.com
Japan	PCNJapanContact@list.ti.com